

# Tuya Wireless Controlled Devices

GDPR compliance



## YE-880(IOT)-CO (t) Carbon Monoxide Alarm

Energy Saving version: power supply by batteries available.



### Specification:

Measuring Method: Warm up Mode

Measuring Mode: Automatic

Display Mode: LED digital with 3 numerical.

Alarm Mode: Sound & Light on device

Alarming/ alarm on App


Power Supply: AA battery (1.5V) x 3pcs

or by USB port DC5V 0.5A (optional)

**Performance index:** Measuring concentration: 000-999PPM

Concentration	Quality Level	Display on Device	Alarm status
>40-75PPM	Level 1	Lighting for 1 min. then extinguish	No alarm
>75-150PPM	Level 2	Lighting continuous	No alarm
> 150PPM	Level 3	Lighting continuous	Alarm rises

### Instruction for installing:



1. Press "Test" button on device for 6 seconds and release. When indicator led is fast flashing, add the device under App.
2. When install on wall, it will be more convenient by using hanging holes: fix screws on wall firstly and then hang the Detector there.
3. When install on ceiling, use installing holes: with screws insert into the holes, along-with the base of device, fix tightly on the ceiling. Other parts of Detector will be spin tightly to the base accordingly.

4. Not to install the Detector near the air exit, air exchanging fan, room door and any places with more wind flowing volume.

5. Not to install the Detector at any place where can be sprayed by water.

6. Suggestion: install the CO detector inside any room where there will have CO occurring.

### Warm Reminder:

- For the first time installing and using the device, it will be more stable after power on 5 minutes.

- Auto-standby 3 minutes later when no trigger happened.