

Tuya Wireless Controlled Devices

GDPR compliance



YE-880(IOT)-GAS (t) Combustible Gas Detector

Detecting any combustible gas, including natural propane / liquid gas in house



Specification:

Measuring Method: Warm up Mode

Measuring Mode: Automatic

Display Mode: LED digital with 3 numerical.

Alarm Mode: Sound & Light on device

Alarming / alarm on App

Power Supply: USB port 5V 500mA


(3pcs AA battery 4.5V for emergency only)

No WiFi controlled function when power supply from batteries.

Performance index: Measuring concentration: 000-999PPMx10

Concentration	Display on device	Alarm status
>1000-2500PPM	Lighting continuous	No alarm
> 2500PPM	Lighting continuous	Alarm rises

Instruction for installing:



1. Press "Test" button on device for 6 seconds and release. When indicator led is fast flashing, add device under App accordingly.
2. When install on wall, it will be more convenient by using hanging holes: fix screws on wall firstly and then hang the Detector there.
3. When install on ceiling, use installing holes: with screws insert into the holes, along-with the base of device, fix tightly on the ceiling. Other parts of the Alarm will be spin tightly to the base accordingly.

4. Not to install the Detector near the air exit, air exchanging fan, room door and any places with more wind flowing volume.

5. Not to install the Detector at any place where can be sprayed by water.

6. Suggestion: any room using above Gases is suggested to install this detector.

Warm Reminder:

- For the first time installing and using this device, it will be more stable after power on 5 minutes.

- Auto-standby 3 minutes later when no trigger happened.

- After your device detected the capacity exceed the standard index, residual gas maybe still left inside the Sensor that cause deviation under the static status. For settling, power on the device again.