



Tuya Wireless Controlled Devices (GDPR available)

涂鸦智能版产品



产品名称 Devices Name	产品型号 Model No.	产品规格 Specification	产品特点 Features
多功能遥控器 Multifunctional remote controller	YE-880(IOT)-T(t)	电源power supply : USB DC5V 0.5A	可以遥控红外线控制的空调、电视、电风扇、机顶盒等电器。支持亚马逊/谷歌音箱系统/IFTTT/天猫精灵。Remote control of air conditioners, televisions, fans, set-top boxes, etc. Support Amazon/Google Home/IFTTT/TmallGenie.
门磁感应器 Door/Window Sensor	YE-880(IOT)-D(t)	电源power supply : 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs (1.5V) or by USB port DC5V 0.5A	门窗被打开超过10毫米, 手机APP立即报警 When door/window is opened excess 10mm, it will feedback to App with alarm warning
红外线人体感应器 Motion Sensor	YE-880(IOT)-M(t)	电源power supply : 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs (1.5V) or by USB port DC5V 0.5A	探测最大距离10米。 Max. probing distance: within 10M
一氧化碳检测仪 CO detector/ alarm	YE-880(IOT)-CO(t)	电源power supply : 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs (1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
液化石油气检测仪 GAS alarm	YE-880(IOT)-GAS(t)	电源power supply : 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs (1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
烟雾检测仪 Smoke Detector	YE-880(IOT)-SD(t)	电源power supply : 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs (1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
窗帘电机控制盒 Curtain Control Box	YE-880(IOT)-C(t)	电压 Voltage : 100~240V~ 电流 Current : 4A	本产品可以控制外置交流窗帘电机。 This control box can control the exterior installation of AC Curtain Motor.
智能计量插座 Smart Socket	YE-860U-WIFI(t) YE-880*-WIFI(t)	电压 Voltage : 125V~ / 250V~ 电流 Current : 15A / 16A	支持亚马逊/谷歌音箱系统/IFTTT/天猫精灵 Support Amazon/Google Home/IFTTT /TmallGenie
智能插座 Smart Socket	YE-10W1	电压 Voltage : 125V~ 电流 Current : 15A	插孔: wifi单独控制 支持亚马逊/谷歌音箱系统/IFTTT/天猫精灵 socket: wifi controlled independent Support Amazon/Google Home/IFTTT /TmallGenie

支持亚马逊/谷歌音箱系统/IFTTT/天猫精灵
Support Amazon/Google Home/IFTTT/TmallGenie

涂鸦智能 智能生活



涂鸦智能



阿里巴巴店铺二维码



商家店铺二维码



拼多多店铺二维码



Pchome store



Yahoo mall store



momomall

YUEN IN ELECTRONIC FACTORY

惠州悦音电子有限公司

CHINA FACTORY

TEL: 86-752-6610438 6901011 6614777 FAX: 86-752-6610428

E-MAIL: yue98@vip.163.com yuehin@sina.com

2018. 7

From anywhere in the world, by smartphone you can remotely control various facilities at home, and monitor housing situation, such as status of flammable gas, fire and water leak. Providing you better, more convenience and safety living environment.

在世界的任何地方, 藉由智慧手机, 可以远控家中各种设备及监控家中可燃气体及水火险情等状况。提供您更好、更便利及安全的居家环境。



Bassonic

YUEH-IN CO., LTD.

悦音电子股份有限公司

HEAD OFFICE

TE: 886-2-29855541 (REP) FAX: 886-2-29841118 29827863

E-MAIL: yuin@yuin.com.tw HOME PAGE: www.yuin.com.tw



Wifi Controlled Devices: Specification

无线 WiFi 系列产品

悦音博士®
Bassonic

产品名称 Devices Name	产品型号 Model No.	产品规格 Specification	产品特点 Features
 空调遥控器 air-conditioning Remote Controller	YE-880(IOT) -T2 (W)	电源power supply: USB DC5V 0.5A	360°无死角发射, 最大发射距离10米。 No blind angle with 360° transmitting. Max.Remote Control Distance:10M. 最大发射距离10米, transmitting. Max.Remote Control Distance:10M.
	YE-880(IOT) -T1 (W)		
 门磁感应器 Door/Window Sensor	YE-880(IOT) -D(W)	电源power supply: 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs(1.5V) or by USB port DC5V 0.5A	门窗被打开超过10毫米, 手机APP立即报警 When door/window is opened excess 10mm, it will feedback to App with alarm warning
 红外线人体感应器 Motion Sensor	YE-880(IOT) -M(W)	电源power supply: 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs(1.5V) or by USB port DC5V 0.5A	探测最大距离10米。 Max. probing distance: within 10M
 一氧化碳检测仪 CO detector/alarm	YE-880(IOT) -CO(W)	电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 液化石油气检测仪 GAS alarm	YE-880(IOT) -GAS(W)	电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 烟雾检测仪 Smoke Detector	YE-880(IOT) -SD(W)	电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 浸漏水报警器 Water Leakage Alarm	YE-880(IOT) -WL(W)	电源power supply: 电池AA 1.5VX3 AA batteriesX3pcs(1.5V)	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 高清摄像头 Wireless monitor IP Camera	YE-880(IOT) -V1&V2(W)	分辨率 Resolution: 720P (25fps) VGA (30fps)	支持一键WiFi连接 Support "One Key WiFi Configuration"
 窗帘电机控制盒 Curtain Control Box	YE-880(IOT) -C(W)	电压 Voltage: 100-240V~ 电流Current : 4A	本产品可以控制外置交流窗帘电机。 This control box can control the exterior installation of AC Curtain Motor.
 计量智能插座 Smart Socket	YE-860U-2WIFI YE-880*-2WIFI	电压Voltage: 125V~/250V~ 电流Current: 15A/16A	计量和计算 monitoring&calculating
	YE-3200*- 2WIFI	电压Voltage: 250V~ 电流Current: 16A	计量和计算 monitoring&calculating

for all Android phone for google play for Apple Store



YE-3200*-WIFI

电压Voltage: 250V~
电流Current: 16A

插孔: wifi单独控制
socket: wifi controlled
independent



2.4G Wireless Remote Control Operation for IOT kit

无线 IOT 系列产品

悦音博士®
Bassonic

产品名称 Devices Name	产品型号 Model No.	产品规格 Specification	产品特点 Features
 空调遥控器 air-conditioning Remote Controller	YE-880(IOT) -T	电源power supply: USB DC5V 0.5A	360°无死角发射, 最大发射距离10米。 No blind angle with 360° transmitting. Max.Remote Control Distance:10M.
 门磁感应器 Door/Window Sensor	YE-880(IOT) -D	电源power supply: 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs(1.5V) or by USB port DC5V 0.5A	门窗被打开超过10毫米, 手机APP立即报警 When door/window is opened excess 10mm, it will feedback to App with alarm warning
 红外线人体感应器 Motion Sensor	YE-880(IOT) -M	电源power supply: 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs(1.5V) or by USB port DC5V 0.5A	探测最大距离10米。 Max. probing distance: within 10M
 一氧化碳检测仪 CO detector/alarm	YE-880(IOT) -CO	电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 液化石油气检测仪 GAS alarm	YE-880(IOT) -GAS	电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 烟雾检测仪 Smoke Detector	YE-880(IOT) -SD	电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A	报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App
 窗帘电机控制盒 Curtain Control Box	YE-880(IOT) -C	电压 Input Voltage: 100-240V~ 电流Current ampere: 4A	本产品可以控制外置交流窗帘电机。 This control box can control the exterior installation of AC Curtain Motor.
 智能插座 Smart Socket	YE-880*(IOT) -S	电压Voltage: 125V~ 电流Current: 15A	有多种国家规格插座。 Socket with various countries standard are available.
 灯控开关 Lighting Control Box	YE-880(IOT) -L	电压Voltage: 250V 功率 Rating Power: 400W	手机可以通过产品控制灯的开关及定时 Switch on/off and set time for the lamp from App on smart-phone
 七彩灯 Intelligent LED Lamp	YE-880(IOT) -LP	电压 Operating Voltage: 100-240V~ 功率 Rating Power: 6W 灯口规格 Base holder: E27	智能模式: 色彩缤纷/色彩调制/定时/调光等 Intelligent mode: colorful colors / color modulation / light-dimming / timing function
 PM2.5空气检测仪 PM2.5 concentrations alarm	YE-880(IOT) -PM	电源power supply: USB DC5V 0.5A	监测室内PM2.5空气指数, 具有回报及报警功能 detect Air Quality Index(PM2.5) in house and with feedback & alarm function
 控制中心 Control Center	YE-880(IOT) -01	电源power supply: USB DC5V 0.5A	用于连接APP, 以便可以连接各种副产品 For connecting to App so as to remotely control the slave devices
 多功能主插座 Multi-functional Main Socket	YE-880*(IOT)	电压Voltage: 125V~ 电流Current: 15A	有多种国家规格插座, 兼有用于连接APP, 以便可以连接各种副产品 Socket with various countries standard are available. Also can connect to App for remotely controlling slave devices