

2.4G Wireless Operation for IOT kit



2.4G Wireless Remote Control Operation for IOT kit



无线 IOT 系列产品

| 产品名称 Devices Name | 产品型号 Model No. | 产品规格 Specification | 产品特点 Features |
|--|---------------------|---|--|
| 空调遥控器 air-conditioning Remote Controller | YE-880(IOT) -T | 电源power supply: USB DC5V 0.5A | 360°无死角发射, 最大发射距离 10米。 No blind angle with 360° transmitting. Max.Remote Control Distance:10M. |
| 门磁感应器 Door/Window Sensor | YE-880(IOT) -D | 电源power supply: 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs(1.5V) or by USB port DC5V 0.5A | 门窗被打开超过10毫米, 手机APP 立即报警 When door/window is opened excess 10mm, it will feedback to App with alarm warning |
| 红外线人体感应器 Motion Sensor | YE-880(IOT) -M | 电源power supply: 电池AAA 1.5VX2或USB 5V 0.5A AAA batteriesX2pcs(1.5V) or by USB port DC5V 0.5A | 探测最大距离10米。 Max. probing distance: within 10M |
| 一氧化碳检测仪 CO detector/alarm | YE-880(IOT) -CO | 电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A | 报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App |
| 液化石油气检测仪 GAS alarm | YE-880(IOT) -GAS | 电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A | 报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App |
| 烟雾检测仪 Smoke Detector | YE-880(IOT) -SD | 电源power supply: 电池AA 1.5VX3或USB 5V 0.5A AA batteriesX3pcs(1.5V) or by USB port DC5V 0.5A | 报警方式: 声光/手机APP Alarm Mode: Sound & Light Alarming / alarm on App |
| 窗帘电机控制盒 Curtain Control Box | YE-880(IOT) -C | 电压 Input Voltage: 100-240V~ 电流Current ampere: 4A | 本产品可以控制外置交流窗帘电机。 This control box can control the exterior installation of AC Curtain Motor. |
| 智能插座 Smart Socket | YE-880(IOT) -S | 电压Voltage: 125V~ 电流Current: 15A | 有多种国家规格插座。 Socket with various countries standard are available. |
| 灯控开关 Lighting Control Box | YE-880(IOT) -L | 电压Voltage: 250V 功率 Rating Power: 400W | 手机可以通过产品控制灯的开关 及定时 Switch on/off and set time for the Lamp from App on smart-phone |
| 七彩灯 Intelligent LED Lamp | YE-880(IOT) -LP | 电压 Operating Voltage: 100-240V~ 功率 Rating Power: 6W 灯口规格 Base holder: E27 | 智能模式: 色彩缤纷/色彩调制 /定时/调光等 Intelligent mode: colorful colors / color modulation / light-dimming / timing function |
| PM2.5空气检测仪 PM2.5 concentrations alarm | YE-880(IOT) -PM | 电源power supply: USB DC5V 0.5A | 监测室内PM2.5空气指数, 具有回报 及报警功能 detect Air Quality Index(PM2.5) in house and with feedback & alarm function |
| 控制中心 Control Center | YE-880(IOT) -01 | 电源power supply: USB DC5V 0.5A | 用于连接APP, 以便可以连接各种副产品 For connecting to App so as to remotely control the slave devices |
| 多功能主插座 Multi-Functional Main Socket | YE-880(IOT) | 电压Voltage: 125V~ 电流Current: 15A | 有多种国家规格插座, 兼有用于连接 APP, 以便可以连接各种副产品 Socket with various countries standard are available. Also can connect to App for remotely controlling slave devices |