

2.4G Wireless Controlled Devices

Need a Control Center (gateway) connecting to App firstly.



YE-880(IOT)-SD Multifunctional Detector

Detecting capacity of Alcohol, Smoke, Isobutane, Methanal and such harmful smoke in house.



Specification:

Measuring Method: Warm up Mode

Measuring Mode: Automatic


Alarm Mode: Sound & Light alarming

Alarm on App

Power Supply: USB port 5V 500mA

(3pcs AA battery 4.5V for emergency only)

Instruction for installing:



Firstly, make sure the Control Center is already configured to App.

1. Turn on the housing of device, use a pin to insert the "Reset" hole located at the back side of device, release around 6 seconds or above later. The indicated led will be fast flashing, then add to App accordingly.
2. When install on side wall, use hanging holes will be more convenient: Firstly fix screws on wall firstly and then hang the Detector there.
3. When install on ceiling, use installing holes: Insert screws into the hanging holes, along-with the base of device, fix tightly on the ceiling. Other parts of the Detector will be spin tightly to the base accordingly.
4. Not to install the Detector near the air exit, air exchanging fan, room door and any places with more wind flowing volume.
5. Not to install the Detector at any place where can be sprayed by water.
6. Suggestion: in each room, for every 25-40 square meters area, install 1 pc of Detector. And for important equipment, 0.5 -2.5M above from it, install 1 pc of Alarm.

Warm Reminder:

- For the first time installing and using this device, it will be more stable after power on 5 minutes.