

Tuya Wireless Controlled Devices

GDPR compliance



YE-880(IOT)-SD (t) Multifunctional Detector

detecting capacity of Alcohol, Smoke, Isobutane, Methanal in house



Specification:

Measuring Method: Warm up Mode

Measuring Mode: Automatic

Alarm Mode: Sound & Light on device


Alarming / alarm on App

Power Supply: USB port 5V 500mA

(3pcs AA battery 4.5V for emergency only)

No WiFi controlled function when power supply from batteries.

Instruction for installing:



1. Press "Test" button on device for 6 seconds and release. When indicator led is fast flashing, add devices under App accordingly.
2. When install on wall, it will be more convenient by using hanging holes: fix screws on wall firstly and then hang the Detector there.
3. When install on ceiling, use installing holes: with screws insert into the holes, along-with the base of device, fix tightly on the ceiling. Other parts of the Alarm will be spin tightly to the base accordingly.
4. Not to install the Alarm near the air exit, air exchanging fan, room door and any places with more wind flowing volume.
5. Not to install the Alarm at any place where can be sprayed by water.
6. Suggestion: in each room, for every 25-40 square meters area, install 1 pc of Alarm. And for important equipment, 0.5 -2.5M above from it, install 1 pc of Detector.

Warm Reminder:

- For the first time installing and using this device, it will be more stable after power on 5 minutes.
- Auto-standby 3 minutes later when no trigger happened.
- Once trigger source is removed after alarming, the device is still not go back to normal status, there may have residual smoke or gas left inside the sensor. For settling, power on the detector again.